| (Under 37 CFR 1.97(d)) | | | | | R.304045 | | |
|---|---|--|-------------------------|---|---|---------------------------------|--|
| In Re Applicatio | n Of: Bertram S | SUGG | | | | · | |
| Application No. Filing Date Exar | | Examiner | | Customer No. | Group Art Unit | Confirmation N | |
| 10/540,026 | January 25, 2006 | Bryan P. Gore | don | 02219 | 2834 | 8866 | |
| Title: | PIEZOELECTRIC A | ACTUATOR AND A | METHOI | FOR ITS MAI | NUFACTURE | | |
| 1.97(c), an | nation Disclosure Staten d on or before payment I the fee set forth in 37 C | Commission nent submitted here of the issue fee, and | with is b | eing filed after | | | |
| ☐ A ched | k in the amount of | is attac | hed. | | | | |
| | irector is hereby authorize | ed to charge and cre | edit Depos | it Account No. | 07-2100 | | |
| as des | scribed below. Charge the amount o | F \$180.00 | | | | | |
| . 🗆 | Credit any overpayme | | - | | • | | |
| | Charge any additiona | | | | | | |
| ☐ Pavme | ent by credit card. Form F | · | d. | | | | |
| WARN | IING: Information on the led on this form. Provid | is form may becom | e public. | Credit card inf | ormation shoul n on PTO-2038. | d not be | |
| Certi | ficate of Transmission by | Facsimile* | 1.1.4 | Certificate of M | Iailing by First C | lass Mail | |
| account is b | his document and authorizatio eing facsimile transmitted to rademark Office) on | | with t as fi "Com | he United States F rst class mail | correspondence is Postal Service with s in an envelope nts, P.O. Box 1450 [8(a)] on | sufficient postage addressed to | |
| Signature | | | | Signature of Person Mailing Correspondence | | | |
| Typed or Printed Name of Person Signing Certificate | | | | Typed or Printed Name of Person Mailing Certificate | | | |
| *This certi deposit ac | ficate may only be used if count. Signature Ronald E. Greigg Registration No. 31 | | Dated | : March 11, 20 | 008 | | |
| 1423 Powha Alexandria, | GREIGG, P.L.L.C. tan Street, Suite 1 | | | | | | |

Telephone : (703) 838-5500 Facsimile : (703) 838-5554

cc:



Application No.

10/540,026

Confirmation No.8866

Applicant(s)

Bertram SUGG

Filed

January 25, 2006

TC/A.U.

2834

Examiner

Bryan P. Gordon

Docket No.

R.304045

Customer No.

02119

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Date: March 11, 2008

INFORMATION DISCLOSURE STATEMENT UNDER 37 CFR 1.97(d), AND EXPLANATION OF THE RELEVANCE OF THE CITED PRIOR ART

Sir:

The undersigned hereby requests that the prior art cited on the attached prior art statement be placed of record in the application file.

This citation of prior art is made under 37 CFR 1.97(d), since it is being filed after the mailing date of a Final Action, and is being accompanied by the fee of \$180 as set forth in 37 CFR 1.17(p).

The undersigned asserts that each item of information contained in this information disclosure statement was first cited in a communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of this information disclosure statement.

The relevance of the prior art cited on the attached form PTO/SB/08a is as follows:

DE 198 60 001 A1

The invention shows a piezoelectric component, comprising electrically insulating material-containing interspaces (20) between piezoceramic layers (12), is new. A piezoelectric component comprises a stack (11) of at least two ceramic layers (12) with an interposed electrode layer (131, 132), an interspace (20) containing an electrically insulating material (21) being provided between the ceramic layers (12). An Independent claim is also included for production of the above piezoelectric component. Preferred Features: The insulating material (21) is a gas or a plastic and the ceramic layers (12) consist of lead zirconate-titanate.

DE 199 31 927 A1

No abstract available for this patent. It is cited to show state of the art.

DE 600 12 805 T2

The invention shows a porcelain insulator main body and a coating layer formed on a surface of the porcelain insulator main body, the coating layer being made of porcelain raw materials including mainly materials of high dielectric constant and having a relative dielectric constant larger than 4, wherein a ration between maximum value and minimum value of relative dielectric constants at micro portions in the coating layer along a thickness direction of the coating layer is smaller than 2. The porcelain insulator mentioned above can be manufactured by the steps of: (1) preparing said porcelain insulator main body; (2) preparing coating materials as a slurry by (a) grinding raw materials and mixing a clay therein to prepare porcelain raw materials made of 50-60 wt% of SiO2, 20-30 wt% of Al2O3 and a remainder of MgO, CaO, K2O, Na2O, (b) preparing materials of high dielectric constant having a relative dielectric constant larger than 10 separately; and (c) mixing 100 parts by weight of the thus prepared porcelain raw materials and 3-10 parts by weight of the thus prepared materials of high dielectric constant; (3) applying the thus prepared coating materials on a surface of the porcelain main body; and (4) firing the porcelain main body in which the coating materials are applied on its surface.

JP 8-45346

The purpose of this invention is to provide dielectric porcelain which is sintered at a temperature as low as 1000 deg.C or less and has a high dielectric constant and sufficient mechanical strength by specifying the secondary-phase content and the etching thickness of lead-series complex perovskite dielectric porcelain. This lead-series complex perovskite dielectric porcelain has an etching thickness of 0.1 to 0.15mu when etched with an etchant with a pH of 2.0 or less, and has a secondary-phase content of 1.0% or less as represented by secondary-phase content(%)=(the sum of the main peak strength of each secondary phase)/(the sum of the main peak strength of each secondary please + the main peak strength of the main phase) according to X-ray diffraction analysis data. The etchant with a pH of 2 or less made from hydrofluoric acid or nitric acid is used, and the etching thickness can be attained by 5 to 10 seconds of etching.

JP 2001-135871

The purpose of this invention is to provide a manufacturing method for a reliable laminated piezoelectric body, with a cost suppressed while corresponding to application, by forming an even ceramics coating layer at a part where the end surface of an internal electrode layer of the laminated piezoelectric body is exposed. A laminated piezoelectric body 1 has a structure where a piezoelectric ceramics layer 2 and internal electrode layer 3 are alternately laminated by plural numbers, with the end surface of internal electrode layer 3 exposed on the side surface, etc. Here, after a green sheet comprising piezoelectric ceramics and the internal electrode layer 3 are alternately laminated by plural numbers to form a green sheet laminated body of a specified shape, its outside surface is coated with ceramics, and de-binding and sintering are performed so that a ceramics coating layer 4 is formed at a part where the end surface of internal electrode layer 3 is exposed. The ceramics coating layer 4 is formed by a method suitable for required characteristics.

The Commissioner is hereby authorized to charge payment of the fee of \$180, or any/all fees associated with this communication to Deposit Account 07-2100.

Further examination of this application is respectfully requested.

Respectfully submitted,

Ronald E. Greigg
Registration No. 31.51

Attorney for Applicant(s)

GREIGG & GREIGG, P.L.L.C. 1423 Powhatan Street Unit One Station Square Alexandria, VA 22314

Tel: 703-838-5500 Fax: 703-838-5554

Customer No. 02119

REG/qh Enclosures J:\Bosch\R304045\IDS 1.97(d).wpd